

# CONOSTAN<sup>®</sup>

## Oil Analysis Standards

A Division of **SCP SCIENCE**



MK-VISCOSITY\_BOOK-4.0-E

# VISCOSITY STANDARDS

[www.scpscience.com](http://www.scpscience.com) • [www.conostan.com](http://www.conostan.com)

.....

# CONOSTAN®

## VISCOSITY STANDARDS

.....

The same product reliability and stability that our customers trust in metallo-organic standards are now available in General Purpose Viscosity standards. These certified, mineral oil based, viscosity standards were developed for calibration and verification of all types of viscometers, including glass capillary viscometers, rotational viscometers, cup and falling ball viscometers.

All standards are traceable to National Standards in accordance to ASTM & IP methods. Each standard carries a two year stability guarantee. The determination of kinematic and dynamic viscosity were made in accordance with ASTM D 445/446 and ISO 3104/3105, ISO/IEC 17025 and are traceable to the NIST (National Institute of Standards and Technology).

All calibrations are based on a master viscometer procedure located in ASTM D 2162 and the National Institute of Standards and Technology (NIST) value of 1.0016 mPa.s (centipoise) for water at 20°C (68°F). Custom standards are available. Please contact us for more information.

Viscosity Standards	Volume				
	125 ml	500 ml	1 Litre	4 Litre	20 Litre
<b>S3</b>	150-600-351	150-600-352	150-600-353	150-600-354	150-600-355
<b>S6</b>	150-600-141	150-600-142	150-600-143	150-600-144	150-600-145
<b>N4</b>	150-600-441	150-600-442	150-600-443	150-600-444	150-600-445
<b>N10</b>	150-600-181	150-600-182	150-600-183	150-600-184	150-600-185
<b>S20</b>	150-600-221	150-600-222	150-600-223	150-600-224	150-600-225
<b>N35</b>	150-600-261	150-600-262	150-600-263	150-600-264	150-600-265
<b>N44</b>	150-600-461	150-600-462	150-600-463	150-600-464	150-600-465
<b>S60</b>	150-600-301	150-600-302	150-600-303	150-600-304	150-600-305
<b>N100</b>	150-600-341	150-600-342	150-600-343	150-600-344	150-600-345
<b>S200</b>	150-600-231	150-600-232	150-600-233	150-600-234	150-600-235
<b>N350</b>	150-600-361	150-600-362	150-600-363	150-600-364	150-600-365
<b>N415</b>	150-600-471	150-600-472	150-600-473	150-600-474	150-600-475
<b>S600</b>	150-600-241	150-600-242	150-600-243	150-600-244	150-600-245
<b>N1000</b>	150-600-371	150-600-372	150-600-373	150-600-374	150-600-375
<b>S2000</b>	150-600-381	150-600-382	150-600-383	150-600-384	150-600-385
<b>N4000</b>	150-600-391	150-600-392	150-600-393	150-600-394	150-600-395
<b>S8000</b>	150-600-401	150-600-402	150-600-403	150-600-404	150-600-405
<b>N15000</b>	150-600-411	150-600-412	150-600-413	150-600-414	150-600-415
<b>S30000</b>	150-600-421	150-600-422	150-600-423	150-600-424	150-600-425

# TYPICAL SPECIFICATIONS FOR CONOSTAN<sup>®</sup> VISCOSITY STANDARDS

	Kinematic Viscosity in mm <sup>2</sup> /s (Centistokes)									Saybolt Viscosity
	20 °C/ 68 °F	25 °C/ 77 °F	37.78 °C/ 100 °F	40 °C/ 104 °F	50 °C/ 122 °F	60 °C/ 140 °F	80 °C/ 176 °F	98.89 °C/ 210 °F	100 °C/ 212 °F	
<b>S3</b>	4.5	4.0	3.0	2.8	2.4	2.0	1.5	1.2	1.2	
<b>S6</b>	10	8.8	6.0	5.7	4.5	3.6	2.5	1.9	1.9	
<b>N4</b>	6.7	5.8	4.2	4.0	3.2	2.6	1.9	1.5	1.4	
<b>N10</b>	21	17	11	10	7.5	5.8	3.7	2.7	2.6	
<b>S20</b>	46	35	20	18	13	9.0	5.6	3.6	3.5	87
<b>N35</b>	90	67	36	32	21	15	8.4	5.4	5.3	167
<b>N44</b>	110	86	48	44	30	21	12	7.6	7.4	220
<b>S60</b>	160	119	60	54	35	26	12	7.7	7.5	281
<b>N100</b>	318	228	110	97	60	39	20	11	11	509
<b>S200</b>	715	487	206	180	103	64	30	17	16	954
<b>N350</b>	1400	940	370	330	180	110	46	24	23	1730
<b>N415</b>	1900	1200	480	410	220	130	55	29	28	2200
<b>S600</b>	2400	1600	600	520	280	160	66	34	32	
<b>N1000</b>	5100	3300	1200	1000	520	290	110	52	50	
<b>S2000</b>	8200	5200	1900	1600	780	400	150	70	68	
<b>N4000</b>	18000	11000	3900	3300	1600	840	280	123	117	
<b>S8000</b>	37000	23000	7900	6700	3200	1600	520	210	200	
<b>N15000</b>	64000	40000	13000	11000	5300	2700	850	340	320	
<b>S30000</b>		80000	28000	23000	11000	5800	1700	670	640	



.....

## TYPICAL SPECIFICATIONS FOR CONOSTAN® VISCOSITY STANDARDS (CONT'D)

.....

Dynamic Viscosity in mPa.S (Centipoise)										Saybolt Viscos- ity
	20 °C/ 68 °F	25 °C/ 77 °F	37.78 °C/ 100 °F	40°C/ 104 °F	50 °C/ 122 °F	60 °C/ 140 °F	80 °C/ 176 °F	98.89 °C/ 210 °F	100 °C/ 212 °F	37 °C/ 100 °F
<b>S3</b>	3.7	3.3	2.4	2.3	1.9	1.6	1.2	0.9	0.9	
<b>S6</b>	8.7	7.3	5.0	4.7	3.6	2.9	2.0	1.5	1.4	
<b>N4</b>	5.6	4.8	3.4	3.2	2.6	2.1	1.5	1.1	1.1	
<b>N10</b>	18	14	9.0	8.4	6.2	4.7	3.0	2.1	2.1	
<b>S20</b>	40	30	17	15	11	7.6	4.7	2.9	2.9	87
<b>N35</b>	78	59	31	28	18	13	7.0	4.4	4.3	167
<b>N44</b>	91	71	39	36	24	17	9.4	6.0	5.8	220
<b>S60</b>	138	102	52	46	30	22	9.9	6.3	6.1	281
<b>N100</b>	276	197	94	83	51	33	16	9.4	9.1	509
<b>S200</b>	613	416	174	152	87	54	24	15	13	954
<b>N350</b>	1200	810	320	280	150	92	38	20	19	1730
<b>N415</b>	1600	1100	410	350	190	110	45	23	23	2200
<b>S600</b>	2100	1400	510	440	240	140	55	28	26	
<b>N1000</b>	4400	2800	1000	940	440	240	92	43	41	
<b>S2000</b>	7200	4500	1600	1400	670	340	130	58	56	
<b>N4000</b>	16000	9700	3400	2900	1400	720	240	100	98	
<b>S8000</b>	33000	20000	6900	5900	2800	1400	440	180	170	
<b>N15000</b>	57000	36000	11000	9700	4700	2400	730	290	270	
<b>S30000</b>		72000	25000	20000	9700	5100	1500	570	550	



# TYPICAL SPECIFICATIONS FOR CONOSTAN® VISCOSITY STANDARDS (CONT'D)

Density in g/ml in accordance with ASTM D7042									
	20 °C/ 68 °F	25 °C/ 77 °F	37.78 °C/ 100 °F	40°C/ 104 °F	50 °C/ 122 °F	60 °C/ 140 °F	80 °C/ 176 °F	98.89 °C/ 210 °F	100 °C/ 212 °F
<b>S3</b>	0.833	0.830	0.821	0.820	0.813	0.806	0.792	0.779	0.778
<b>S6</b>	0.831	0.828	0.819	0.818	0.811	0.805	0.791	0.779	0.778
<b>N4</b>	0.834	0.831	0.822	0.820	0.814	0.807	0.793	0.780	0.780
<b>N10</b>	0.842	0.839	0.831	0.829	0.823	0.816	0.804	0.791	0.791
<b>S20</b>	0.871	0.868	0.860	0.859	0.852	0.846	0.833	0.821	0.820
<b>N35</b>	0.872	0.869	0.861	0.860	0.853	0.847	0.834	0.823	0.822
<b>N44</b>	0.828	0.825	0.817	0.816	0.809	0.803	0.791	0.779	0.779
<b>S60</b>	0.863	0.860	0.852	0.851	0.845	0.839	0.826	0.815	0.814
<b>N100</b>	0.867	0.864	0.857	0.855	0.849	0.843	0.831	0.820	0.819
<b>S200</b>	0.858	0.855	0.847	0.846	0.840	0.834	0.822	0.910	0.810
<b>N350</b>	0.863	0.860	0.852	0.851	0.845	0.839	0.827	0.816	0.815
<b>N415</b>	0.865	0.862	0.854	0.853	0.847	0.841	0.830	0.819	0.818
<b>S600</b>	0.866	0.864	0.856	0.855	0.849	0.843	0.832	0.820	0.820
<b>N1000</b>	0.872	0.869	0.862	0.860	0.855	0.849	0.837	0.826	0.826
<b>S2000</b>	0.876	0.873	0.865	0.864	0.858	0.853	0.841	0.831	0.830
<b>N4000</b>	0.882	0.879	0.872	0.871	0.865	0.860	0.849	0.838	0.838
<b>S8000</b>	0.888	0.885	0.878	0.877	0.872	0.866	0.855	0.845	0.845
<b>N15000</b>	0.893	0.891	0.884	0.883	0.877	0.872	0.861	0.851	0.851
<b>S30000</b>		0.896	0.889	0.888	0.883	0.877	0.867	0.857	0.857







# **CONOSTAN<sup>®</sup>**

*Oil Analysis Standards*

**Online:** [www.conostan.com](http://www.conostan.com)  
**Email:** [sales@scpscience.com](mailto:sales@scpscience.com)  
**Order Online at:** [www.scpscience.com](http://www.scpscience.com)

## **NORTH AMERICA**



Tel: (800) 361 6820 • +1 (514) 457 0701  
Fax: (800) 253 5549 • +1 (514) 457 4499

## **FRANCE**

Tel: +33 (0) 1 69 18 71 17  
Fax: +33 (0) 1 60 92 05 67

## **OTHER COUNTRIES & INTERNATIONAL**

Tel: +1 (514) 457 0701  
Fax: +1 (514) 457 4499



More **CONOSTAN<sup>®</sup>** Viscosity Standards  
and their respective specifications coming soon.

Please contact us for updates:  
[sales@scpscience.com](mailto:sales@scpscience.com)